

This listing of claims will replace all prior version, and listings, of claims in the application:

**Listing of Claims:**

1 (original) A self-powered floating water-skimming vessel for use in  
 5 collecting debris on or just below the surface of water, the vessel having a waterline and comprising:  
     two axially-aligned laterally-spaced hulls,  
     propulsion means to drive the vessel in either axial direction,  
     a debris catcher arranged between the said hulls, at least portion of said  
 10 catcher being arranged below the waterline, and said catcher having first and second lateral end openings into which debris can enter and exit depending upon whether the respective opening is leading or trailing having reference to movement of the vessel,  
     a first flap hinged to close the first opening of the catcher, when said  
 15 first opening is the trailing opening so as to block the egress of debris from the catcher, and to open when said first opening is the leading opening to permit ingress of debris into the catcher,  
     a second flap hinged to close the second opening of the catcher, when  
     said second opening is the trailing opening to thereby block the egress of  
 20 debris from the catcher, and to open when said second opening is the leading opening to thereby permit ingress of debris into the catcher.

2 (original) A vessel according to claim 1 having a third flap hingedly-mounted and laterally-arranged between said first and second flaps, such that  
 25 floating debris admitted into the catcher tends to be submerged and wetted as it moves toward the trailing opening.

3 (currently amended) A vessel according to claim ~~1~~ or 2 wherein the  
 30 propulsion means includes a reversible propulsion unit arranged in each hull so that the vessel can be driven in one axial direction or the other when said units are operated ~~in~~-together and to turn the vessel when said units are operated differentially.

4 (original) A vessel according to claim 3 wherein:  
 each propulsion unit is electrically driven,  
 electric batteries are connected to and capable of driving the propulsion  
 units, and

5 solar cells are arranged on the vessel and connected to charge the  
 batteries and/or drive the propulsion units.

5 (currently amended) A vessel according to claim 3 ~~or 4~~ wherein:  
 each propulsion unit comprises an electric motor located within the  
 10 respective hull,  
 a propeller mounted outside the respective hull and  
 magnetic coupling means for transmitting driving torque from the  
 motor to the propeller through the hull.

15 6 (currently amended) A vessel according to ~~any preceding claim 1~~  
 wherein;  
 sensor means is mounted on or in each end of each hull for detecting  
 contact between the respective hull and an obstacle ahead of the vessel's  
 direction of travel,  
 20 control means is provided to connect said sensor means to said  
 propulsion means to effect reversal and/or turning of the vessel upon detection of said  
 contact.

7 (original) A vessel according to claim 6 wherein the sensor means  
 25 comprises:  
 a moveable magnet arranged on the outside of the hull and adapted to  
 be displaced with respect to the hull upon contact with an object, and  
 a magnetically operable electrical switch mounted within the hull  
 adjacent said magnet for operation by the movement of the magnet.

30 8 (currently amended) A vessel according to claim 6 ~~or 7~~ wherein said  
 sensor means is located on or below the waterline on the end of the respective  
 hull.

9 (currently amended) A vessel according to claim 6, ~~7 or 8~~ wherein said control means causes the vessel to cover substantially the whole surface of a rectangular swimming pool over a period of time.

5 | 10 (currently amended) A vessel according to ~~any one of claims 6 to 9~~ wherein said control means effects the reversal of the propulsion unit in one hull for a predetermined time when the sensor means at either end of said hull detects contact with an object.

10 | 11 (currently amended) A vessel according to ~~any preceding claim 1~~ wherein at least portion of the catcher or said flaps is formed from or coated with hydrophobic and/or oleophilic material to facilitate the collection of floating oil on the surface of the water within the catcher.

15 12 (original) A water skimming system for use with a swimming pool having a peripheral wall that extends upwards above the level of pool water including:  
a water skimming vessel as claimed in any preceding claim,  
docking means provide for mounting on the wall of the swimming pool  
20 so as to extend below the level of the pool water, and  
homing means in the vessel adapted to direct the vessel into said docking means to effect emptying of the catcher or recharging of batteries in the vessel.

25 13 (original) A water skimming system according to claim 12 for use with a swimming pool having a skimmer box or like water outlet formed in the wall of the pool and wherein said docking means is adapted for mounting in front of the water outlet so that pool water leaving the pool is directed to flow through the docking means, whereby water leaving the pool will flow through  
30 the catcher of a vessel located in the docking means to effect the emptying of debris from the catcher into the water outlet.

14 (original) A water skimming system according to claim 13 wherein the vessel or the dock includes flap release means to release the leading flap of the catcher so that it can swing outwardly of the catcher to facilitate flow of debris from the catcher of a docked vessel .

5

15 (currently amended) A system according to claim 13 ~~or 14~~ wherein the docking means includes:

power supply means for effecting the charging of batteries on a vessel docked therein, and

10 a homing beacon detectable by the homing means on the vessel, said homing means being connected to the control unit for directing the vessel to the docking means.

16 (original) A system according to claim 15 wherein:

15 the homing beacon comprises a directional radiation emitter, the homing means comprises a directional radiation detector adapted to selectively detect the radiation emitted by the emitter, and

the docking means or the homing means includes light sensitive switch means adapted to disable the homing function in ambient sunshine sufficient to charge the batteries of the vessel from the solar power unit.

20

17 (original) A system according to claim 16 wherein:

the homing means comprises a directional radiation emitter and detector,

25 the homing beacon comprises a directional radiation reflector, and the homing means includes light sensitive switch means adapted to disable the homing function in ambient sunshine sufficient to charge the batteries of the vessel from the solar power unit.

30 18 (currently amended) A water skimming system according to ~~any one of~~ claims 12 ~~to 17~~, wherein:

the docking means includes latching means for holding the vessel in the dock to permit discharge of debris from the catcher or recharging of the batteries in the vessel.

19 (currently amended) A water skimming system according to ~~any one of~~  
claims 12 ~~to 18~~ wherein:

the docking means includes a power transmitter connected to the power  
5 supply, and

the vessel includes a power receiver connected to charge the batteries  
of the vessel,

power transmission is initiated upon latching of the vessel in the dock.

10 20 (original) A method of removing floating debris from a swimming pool  
having a peripheral wall containing an outlet opening at the level of water in  
the pool, the method comprising the steps of:

operating in the pool a self-powered floating skimmer vessel having a  
catcher for collecting debris,

15 causing the vessel to dock with docking means arranged in front of the  
outlet opening, and

discharging collected debris from the catcher into pool water flowing  
into the outlet while the vessel is docked.

20 21 (original) A method according to claim 20 wherein the vessel is  
powered by solar cells and batteries and the debris catcher has front and rear  
flaps, the method comprising the steps of:

propelling the vessel over the surface of the pool water with the front  
flap open to permit debris to enter the catcher, and with the rear flap closed to  
25 inhibit debris from leaving the catcher,

permitting or causing the front and rear flaps to open when the vessel is  
docked so that the pool water flowing into the outlet carries debris out of the  
catcher and into the pool outlet, and

charging the batteries in the vessel while it is docked.

30